

County Surveyor's Record, Douglas County, Oregon

25853

Resurvey S. Bdy. T.27 S., R. 7 W.
(Hathorn Survey)

CHAINS

from which (old bearing trees)

A white oak, now 22 ins. diam., bears S. 26*W., 18 lks. dist., old blaze opened, not remarked.

A white oak, now 22 ins. diam., bears N.25*W., 18 lks. dist., old blaze opened, not remarked.

Thence

N.89*50'W.

Descend W.slope, 68 ft.

4.50 Looking Glass-Reston road, bears NE. and SW.

10.00 Foot of descent; thence level.

21.00 Begin ascent of E. slope, 56 ft.

27.04 Intersect W. bdy. of original sec 6.

At this point

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for NE. cor. of T. 28 S., R. 7 $\frac{1}{2}$ W., with brass cap marked

S6
T28S
R7 $\frac{1}{2}$ W
1924

from which

A fir, 24 ins. diam., bears S.24 $\frac{1}{2}$ *W., 46 lks. dist., marked T 28 S R 7 $\frac{1}{2}$ W S 6 B T.

A fir, 12 ins. diam., bears S.65 $\frac{1}{2}$ *W., 31 lks. dist., marked T 28 S R 7 $\frac{1}{2}$ W S 6 B T.

Ford's original standard cor. of T. 28 S., Rs. 7 and 8 W., re-established as NW. cor. of T. 28 S., R. 7 W., hereafter described, bears N.0*41'E., 8.78 chs. dist.

32.80 Intersect the cor. established by Hathorn for standard cor. of T. 28 S., Rs. 7 and 8 W., located by measurement from the original bearing trees. Old blaze on SE. tree has been opened and marks are plain. SW. tree is a decayed stump, old blazes visible.

At the exact cor. point

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for cor. of T. 28 S., Rs 7 $\frac{1}{2}$ and 8 W., with