

CHAINS

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 27, 28, 33, and 34, with brass cap marked

T27S	R7W
S28	S27
S33	S34
AP 1	
1924	

from which

(Old bearing tree) A black oak, now 20 ins. diam., bears N.1*E., 120 lks. dist., marked T 27 S R 7 W S 27 B T.

(New bearing tree) A fir, 8 ins. diam., bears S.27*E., 21 lks. dist., marked T 27 S R 7 W S 34 B T.

(New bearing tree) A fir 12 ins. diam., bears S.29*W., 12 lks dist., marked T 27 S R 7 W S 33 B T.

(Old bearing tree) A black oak, now 24 ins. diam., bears N. 17*W., 100 lks. dist., re-marked T 27 S R 7 W S 28 B T.

Old bearing tree, an oak, 24 ins. diam., bears S. 49*W., 128 lks. dist.

Original position of old bearing tree, an oak, rotted out, Bears S.1*E., 84 lks. dist.

Thence

N.89*59'W., bet. secs. 28 and 33.

Over rolling land, through heavy timber and dense undergrowth.

Descend 577 ft. over general W. slope, to sec. cor.

39.84 Intersect the 1/4 sec. cor., located by measurement from the original bearing trees, old marks plain. The SW. tree is dead.

At the exact cor. point.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4	S28
	S33
AP 2	
1924	