

Resurvey of Sec. 33, T. 27 S., R. 7 W.

CHAINS

- 29.95 Wire fence, bears E. and W.
- 37.10 Head of dry ravine or draw, course SW.
- 40.01 Intersect the $\frac{1}{4}$ sec. cor., located by record bearing and distance from the original NW. bearing tree, old blaze open and marks plain. Old bearing tree in sec. 34 is not found.
- At the exact cor. point
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- $\frac{1}{4}$
 AP 13
 S33 | S34
 1924
- from which (new bearing trees)
- A black oak, 18 ins. diam., bears N.44 $\frac{3}{4}$ *E., 230 lks. dist., marked $\frac{1}{4}$ S 34 BT.
- A black oak, 20 ins diam., bears N.26*W., 61 lks. dist., marked $\frac{1}{4}$ S 33 B T.
- Original bearing tree, an oak, now 28 ins. diam., bears N.76*W., 39 lks. dist.
- Thence from the $\frac{1}{4}$ sec. cor.
- N.0*07'E., bet. secs. 33 and 34.
- Ascend 494 ft. on S. slope to spur.
- 20.45 Wire fence, bears E. and W.
- 24.72 Top of Spur, slopes SW.; descend 126 ft. on NW. slope.
- 38.10 Dry Ravine, course W.; ascend 10 ft. on SE. slope.
- 39.98 Intersect the cor. of secs. 27, 28, 33, and 34, heretofore described.
- Land, rolling and mountainous.
- Soil, clay loam, 1st and 2nd gate.
- Timber, fir, oak, laurel, and pine.
- Undergrowth, oak, laurel, hazel, and fir.