

County Surveyor's Record, Douglas County, Oregon

5865

Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. Par. S.)  
(Ford Survey)

CHAINS

SI:S6  
R7W:R6W  
T28S  
SC  
1924

from which (new bearing trees)

A black oak, 6 ins. diam., bears S.36°E. 61 lks.  
dist marked S C T 28 S R 6 W S 6 B T.

Thence

S.89°55'W., along N. bdy. of sec. 1.

Descend general W. slope, 121 ft. through scattered  
clumps of brush and timber.

5.45 Wire fence, bears NE. and SW.

7.46 Intersect the cor. of Tps. 27 S., Rs. 6 and 7 W., hereto-  
fore described.

Thence from the Tp. cor.

N.89°13'W., along the N. bdy. of sec. 1.

Over nearly level open land, across Looking Glass  
Valley, along fence on S. side of orchard.

12.50 Leave orchard, bears N. and S.; enter grain field.

26.55 Pole fence, bears N. and S.; leave field; enter brush  
and timber.

32.46 Point for standard  $\frac{1}{4}$  sec. cor., located by Hathorn record  
tie from the  $\frac{1}{4}$  sec. cor. of sec. 36.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, for standard  $\frac{1}{4}$  sec. cor., with brass cap marked

CS  $\frac{1}{4}$  SI  
1924

from which

An ash, 10 ins. diam., bears S.64°W., 61 lks. dist.,  
marked S C  $\frac{1}{4}$  S 1 B T.

No other tree available and no stones available for  
mound.

Hathorn's  $\frac{1}{4}$  sec. cor. of sec. 36, heretofore described,  
bears S.87°10'W., 7.50 chs. dist.

Thence, from the standard  $\frac{1}{4}$  sec. cor.,

N.89°43'W., along the N. bdy. of sec. 1.

11.60 Fence, bears N. and S.; leave timber and brush.

14.20 Fence, bears N. and S.; enter orchard.