

Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. Par. S.)
(Ford Survey)

CHAINS

Hathorn cor. of secs. 34 and 35.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for angle point, with brass cap marked
AP
1924

No bearing trees or other objects available, no stones available for mound.

Hathorn's cor. of secs. 34 and 35, heretofore described bears S.15*E., 76 lks. dist.

Thence, from the angle point,

N.89*47'W., along the N. bdy. of sec. 3.

27.00 Fence, bears N. and S.

27.22 Intersect E. bdy. of Daniel Huntley D.L.C.; NE. cor.

bears N.0*02'W., 28.93 chs. dist.; SE. cor. bears S.0*02'E., 35.97 chs. dist.

27.30 Road, bears N. and S.

31.43 Fence, bears N. and S.

32.47 Intersect the point for standard $\frac{1}{4}$ sec. cor. of sec. 3, established by Ford and located by Hathorn's record tie from Hathorn $\frac{1}{4}$ sec. cor. of sec. 34.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for standard $\frac{1}{4}$ sec. cor. of sec. 3, with brass cap marked

SC $\frac{1}{4}$ S 3
1924

No bearing trees or other objects available, no stones available for mound.

Hathorn's $\frac{1}{4}$ sec. cor. of sec. 34, heretofore described, bears S.83*56'W., 7.29 chs. dist.

Thence, from the standard $\frac{1}{4}$ sec. cor.,

S.89*42'W. along the N. bdy. of sec. 3.

7.45 Intersect the point for the $\frac{1}{4}$ sec. cor. of sec. 34, established by Ford and located by Hathorn's record tie from Hathorn $\frac{1}{4}$ sec. cor. of sec. 34.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for angle point, with brass cap marked