

Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. Par. S.)  
(Ford Survey)

CHAINS

AP  
1924

No bearing trees or other objects available, no stones available for mound.

Hathorn's  $\frac{1}{4}$  sec. cor. of sec. 34, heretofore described, bears S.15\*E., 76 lks. dist.

Thence, from the angle point,

N.89\*28'W., along the N. bdy. of sec. 3.

5.43 Wire fence, bears N. and S.; leave orchard; enter timber and brush.

8.68 Dry run, course S.

12.23 Wire fence, bears N. and S.; enter orchard.

17.78 Wire fence, bears N. and S.; leave orchard; enter timber and brush.

19.60 Looking Glass Creek, 30 lks. wide, course S.

Leave valley; ascend S. slope, 100 ft.

26.88 Wire fence, bears N. and S.

29.88 Top of ascent; thence over rolling N. slope.

31.64 Intersect the point for standard cor. of secs. 3 and 4, established by Ford, located by record bearing and measurement from the original SE. bearing tree, and evidence of the original SW. bearing tree.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for standard cor. of secs. 3 and 4, with brass cap marked

S4:S3  
T28S:R7W  
SC  
1924

from which (new bearing trees)

A fir, 24 ins. diam., bears S.56\*E., 13 lks. dist., marked S C T 28 S R 7 W S 3 B T.

A fir, 14 ins. diam., bears S.13\*W., 8 lks. dist., marked S C T 28 S R 7 W S 4 B T.

Original SE. bearing tree, now a rotted and decayed black oak stump, bears S.35\*E., 9 lks. dist.

Depression in the ground, evidently the position of the SW. bearing tree, bears S.12\*W., 30 lks. dist.

Cor. point further evidenced by old decayed stake (oak),