

County Surveyor's Record, Douglas County, Oregon

Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. Par. S.)
(Ford Survey)

CHAINS	<p>marks still legible, set by local surveyor.</p> <p>The cor. established by Hathorn for standard cor. of secs. 3 and 4, restored as angle point, heretofore described, bears S.34*53'W., 113 lks. dist.</p> <p>Land, level in valley; remainder hilly. Soil, clay loam in valley, 1st rate; remainder 2nd rate.</p> <p>Timber, oak and ash in valley; remainder second growth, and scattering old growth fir.</p> <p>Undergrowth, hazel, fir, oak, ash, and willow.</p>
	<p>N.88*27'W., along the N. bdy. of sec. 4.</p> <p>Over rolling mountainous land, through heavy timber and medium undergrowth.</p>
7.38	<p>Intersect the point for the cor. of secs. 33 and 34, established by Ford and located by record bearing and distance from the stump of the original NW. bearing tree. The marks are obliterated by decay, but evidence of the blazes are still distinguishable. No evidence of the NE. bearing tree is found.</p> <p>At the exact cor. point.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for angle point, with brass cap marked</p> <p style="text-align: right;">AP 1924</p> <p>from which (new bearing trees)</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S.66*E., 30 lks. dist., marked A P B T.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S.85*W., 9 lks. dist., marked A P B T.</p> <p>Stump of original NW. bearing tree, a laurel, 18 ins. diam., bears N.65*W., 25 lks. dist.</p> <p>The cor. established by Hathorn for the cor. of secs. 33 and 34, heretofore described, bears S.32*W., 1.37 chs. dist.</p> <p>Thence from the angle point,</p> <p>N.88*55'W., along the N. bdy. of sec. 4.</p>
0.73	<p>Intersect the line bet. secs. 33 and 34, N.0*04'W., 1.18 chs. from the Hathorn cor. of secs. 33 and 34.</p> <p>Ascend NE. slope, 30 ft.</p>
7.75	<p>Top of ascent on N. slope; descend NW. slope, 65 ft.</p>
12.00	<p>Old road, bears N. and S.</p>