

County Surveyor's Record, Douglas County, Oregon

5871
39

Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. par.S.)
(Ford Survey)

CHAINS
12.90

Wire fence, bears N. and S.

13.00

Intersect W. bdy. of Daniel Huntley D.L.C.; NW. cor.

bears N.0°05'W., 28.31 chs. dist.; SW. cor. bears S.0°05'E., 11.61 chs. dist.

21.05

Draw, course N.

27.35

Old road, bears N. and S.

28.50

Creek, 2 lks. wide, course N.

28.75

Fence, bears N. and S.; leave timber and brush.

31.98

Apportioned distance.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap marked

SC $\frac{1}{4}$ S4
1924

*FD. with H. No. 1000000000
M 54-55
6/81- R. DeLan
FD. 7/81 M 73-27 M 28-30*

from which

An ash, 10 ins. diam., bears S.85 $\frac{1}{2}$ °E., 206 lks. dist., marked S C $\frac{1}{4}$ S 4 B T.

A black oak, 6 ins. diam., bears S.75 $\frac{1}{2}$ °W., 208 lks. dist., marked S C $\frac{1}{4}$ S 4 B T.

The cor. established by Hathorn for the standard $\frac{1}{4}$ sec. cor. of sec. 4, restored as angle point, heretofore described, bears S.36°13'W., 1.94 cha. dist.

34.53

Picket fence, bears N. and S.; leave opening; enter timber and brush; ascend E. slope, 110 ft;

35.95

Pole fence, bears N. and S.

37.45

Old road, bears N. and S.

39.29

Top of ascent, bears N. and S.

Intersect the point established by Ford for the $\frac{1}{4}$ sec. cor. of sec. 33, located by measurement from the stumps of the original bearing trees, which are now badly decayed, but showing evidence of the old blazes.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for angle point, with brass cap marked

AP
1924

from which (new bearing trees)