

County Surveyor's Record, Douglas County, Oregon
Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. Par. S.)
(Ford Survey)

5873

4)

CHAINS

from which (new bearing trees)

A laurel. 12 ins. diam., bears S. 72*E., 45 lks. dist.,
marked S C T 28 S R 7 W S 4 B T.

An oak, 4 ins. diam., bears S. 29*E., 12 lks. dist.,
marked S C T 28 S R 7 W S 4 B T.

Original SW. bearing tree, a laurel, 20 ins. diam., bears
S. 30*W., 47 lks. dist.

Evidence of the SE. bearing tree, a fir, bears S. 35*E.,
22 lks. dist.

New NE. cor. of sec. 5, and angle point No. 7 of re-
surveyed sec. 33, heretofore described, bears S. 4*52'E.,
3.30 chs. dist.

The cor. established by Hathorn for standard cor. of secs.
4 and 5, restored as angle point No. 6 of resurveyed
sec. 33, heretofore described, bears S. 35*34'W., 4.06
chs. dist.

Land, rolling and mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, oak, pine, and laurel.

Undergrowth, vinemaple, hazel, laurel, oak, and fir.

N. 89*18'W., on blank line, through sec. 33, along the N.
bdy. of original sec. 5.

Over rolling land, through heavy timber and dense under-
growth.

7.29 Intersect the point for cor. of secs. 32 and 33, es-
tablished by Ford, located by record measurements from
the original bearing trees. The marks on the NE. tree
legible. The blazes on the NW. tree are plain, but
the marks are weathered and decayed away.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for angle point, with brass cap marked

AP
1924

from which (new bearing trees)