

## County Surveyor's Record, Douglas County, Oregon

Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. Par. S.)  
(Ford Survey)

## CHAINS

A fir, 14 ins. diam., bears S.41°E., 35 lks. dist.,

Marked A P B T.

A fir, 8 ins. diam., bears S.50°W., 11 lks. dist.,

marked A P B T.

Original NE. bearing tree, an oak, 16 ins. diam., bears

N.35°E., 14 lks. dist.

Original NW. bearing tree, a laurel, 24 ins. diam., bears

N.5°W., 60 lks. dist.

The cor. of secs. 32 and 33, established by Hathorn, here-

tofore described, bears S.36°25'W., 4.21 chs. dist.

Thence, from the angle point,

N.88°20'W., on blank line, through sec. 33, along the N.

bdy. of original sec 5.

2.52 Intersect the line bet. secs. 32 and 33, N.0°15'W., 3.46

chs. from the cor. of secs. 32 and 33, established by

Hathorn, heretofore described.

Thence continue the same line and measurement on blank

line, through sec. 32, along the N. bdy. of original

sec. 5.

4.65 Dry Draw, course N.; ascend.

7.50 Top of ascent; descend NW. slope, 100 ft.

16.80 Dry draw, course N.; ascend NE. slope, 50 ft.

20.50 Top of small spur, slopes N.; descend NW. slope 20 ft.

25.50 Foot of descent; thence over bench.

31.94 Intersect the point for standard  $\frac{1}{4}$  sec. cor. of sec. 5,

established by Ford, located by measurement from the

original bearing trees. Marks are plain on the NW.

tree. Marks on the SW. tree are overgrown and blazes

not opened.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in

the ground, for witness point, with brass cap marked

WP  
1924

from which

New bearing tree, a laurel, 8 ins. diam., bears

S.65°E., 17 lks. dist., marked W P B T.