

County Surveyor's Record, Douglas County, Oregon

5875

Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. Par. S.)
(Ford Survey)

CHAINS

Original bearing tree, a black oak, 16 ins. diam.,
bears S.74*W. (not S.73.*W.), 39 lks. dist., re-
marked W P B T.

Original bearing tree, a black oak, 12 ins. diam.,
bears N.38*W. (not N.40*W.), 40 lks. dist.

New $\frac{1}{2}$ sec. cor. of sec. 5 only, on center meridional sub-
division line of sec. 5 and on S. bdy. of sec. 32, here-
tofore described, bears S.4*54'E., 4.41 chs. dist.

The $\frac{1}{4}$ sec. cor. of sec. 5, established by Hathorn as
standard $\frac{1}{4}$ sec. cor., restored as angle point, hereto-
fore described, bears S.35*15' W., 5.39 chs. dist.

Thence, from the witness point,

N.88*36'W., on blank line, through sec. 32, along the N.
bdy. of original sec. 5.

7.41 Point for cor. established by Ford for the $\frac{1}{4}$ sec. cor.
of sec. 32, located by Hathorn's record tie from the
Hathorn $\frac{1}{4}$ sec. cor. of sec. 32.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for angle point, with brass cap marked

AP
1924

from which

A fir, 18 ins. diam., bears S.40*E., 15 lks. dist.,
marked A P B T.

A fir, 8 ins. diam., bears S.27 $\frac{1}{2}$ *W., 48 lks. dist.,
marked A P B T.

The $\frac{1}{4}$ sec. cor. of sec. 32, established by Hathorn, here-
tofore described, bears S.33*57'W., 5.50 chs. dist.

Thence, from the angle point,

N.87*38'W., on blank line, through sec. 32, along the N.
bdy. of original sec. 5.

Descend NW. slope, 51 ft.

3.80 Creek, 4 lks. wide, course NW.; ascend NE. slope, 38 ft.

8.15 Top of ascent; descend NW. slope, 240 ft.

26.10 Looking Glass Creek, 30 lks. wide, course NE.; ascend SE.
slope, 130 ft.