

## County Surveyor's Record, Douglas County, Oregon

Resurvey of N. Bdy. T. 28 S., R. 7 W. (6th Std. Par. S.)  
(Ford Survey)

CHAINS  
27.20

Old road, bears NE. and SW.

31.09

Intersect the point for the cor. established by Ford for standard cor. of secs. 5 and 6, located on line bet. original Ford cors. for latitude and by Hathorn's record tie from the Hathorn standard cor. of secs. 5 and 6 for departure.

At the true cor. point thus determined,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, in mound of stone for standard NE. cor. of sec. 6 only, with brass cap marked

|      |
|------|
| S6   |
| T28S |
| R7W  |
| SC   |
| 1924 |

from which

A black oak, 5 in. diam., bears S.  $71\frac{1}{2}^{\circ}$  W., 39 lks. dist., marked S C T 28 S R 7 W S 6 B T.

A fir, 26 ins. diam., bears S.  $48^{\circ}$  W., 86 lks. dist., marked S C T 28 S R 7 W S 6 B T.

The new NW. cor. of sec. 5 on the S. bdy. of sec. 32, heretofore described, bears S.  $4^{\circ}22'$  E., 5.82 chs. dist.

The cor. established by Hathorn for standard cor. of secs. 5 and 6, restored as angle point, heretofore described, bears S.  $38^{\circ}21'$  W., 7.38 chs. dist.

Land, mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, laurel, oak, and pine.

Undergrowth, hazel, vinemapple, laurel, and fir.

N.  $87^{\circ}38'$  W., along the N. bdy. of sec. 6.

Over rolling land, through heavy timber and dense undergrowth,

7.31

Intersect the point for cor. of secs. 31 and 32, established by Ford, located by record bearing and distance from the stump of the original NE. bearing tree, upon which the marks are still legible. The NW. bearing tree has rotted away.