

County Surveyor's Record, Douglas County, Oregon

5879

Resurvey of portion S. Bdy. T. 28 S., R. 7 W.
(Ford Survey)

47

CHAINS

Retracement

From the original cor. of Tps. 28 and 29 S., Rs. 7 and 8 W., established by Ford,

S.89°38½'E., retracing the line bet. secs. 6 and 31.

49.33 The ¼ sec. cor. bet. secs. 6 and 31, bears South, 67 lks. dist.

87.60 Fall 375 lks. S. of the cor. of secs. 5, 6, 31 and 32.

From the Ford cor. of Tps. 28 and 29 S., Rs. 7 and 8 W., re-established as Cor. No. 3 of tract No. 63, identical with Cor. No. 2 of Tract No 47, T 29 S., R. 7 W., hereafter described,

S.88°52'E., resurveying the line bet. secs. 6 and 31.

Over rolling land, through heavy timber and undergrowth.

1.45 Old board fence, bears N. and S.

1.46 Intersect the E. bdy. of T. 28 S., R. 8 W., 17.51 chs.

N. of the Hathorn cor. of Tps. 28 and 29 S., Rs. 8 W., hereafter described.

At the point of intersection

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Tps. 28 and 29 S., R. 7 W., with brass cap marked

T28S
R7W
S31
S6
T29S
1924

from which

A fir, 6 ins. diam., bears N.81½'E., 62 lks. dist., marked T 28 S R 7 W S 31 B T.

A fir, 10 ins. diam., bears S.80½'E., 58 lks. dist., marked T 29 S R 7 W S 6 B T.

2.45 Intersect the W. bdy. of the Wm. McCullough D. L. C. No. 56, at cor. No. 4 of Tract No. 63, hereafter described, which is 13.55 chs. S.0°30'W. from the NW. cor. of said Claim No. 56

2.60 Woven wire fence, bears N. and S.

9.00 Head of draw, course NE.