

## County Surveyor's Record, Douglas County, Oregon

Resurvey of portion S. Bdy. T. 28 S., R. 7 W.  
(Ford Survey)

CHAINS  
20.17

Leave timber; enter grain field, bears NW. and SW.

28.17

Leave grain field; enter heavy timber, bears Nw. and SW.

28.53

Old rail fence, bears NW. and SE.

31.90

Shield Creek, 10 lks. wide, course NE.

39.56

Ten Mile Creek, in bend, 75 lks. wide; course NE.

49.34

Intersect the recognized and accepted  $\frac{1}{4}$  sec. cor., which is a 1 in. iron pipe driven in the ground, set by the county surveyor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S31}{S6}$$

1924

from which

A white oak, 18 ins. diam., bears S.88 $\frac{1}{2}$ \*E., 92 lks. dist., marked  $\frac{1}{4}$  S 6 B T.

A white oak, 16 ins. diam., bears N.16 $\frac{1}{2}$ \*W., 101 lks. dist. marked  $\frac{1}{4}$  S 31 B T.

Thence, from the  $\frac{1}{4}$  sec. cor.

N.83\*46'E., resurveying the line bet. secs. 6 and 31.

1.16

Wire fence, bears NE. and SW.

1.41

Goos Bay highway, bears NE. and SW.

2.00

Board fence, bears NE. and SW.

6.00

Begin steep ascent over NW. slope, 542 ft.

32.00

Woven wire fence, bears N. and S.

38.50

Intersect the point for cor. of secs. 5, 6, 31, and 32, located by measurement from the original bearing trees, on which the blazes and some marks are plain.

At the exact cor. point

Set a basalt stone, 20x12x6 ins., 15 ins. in the ground, in a mound of stone, for cor. of secs. 5, 6, 31, and 32, marked with 5 notches on E. and 1 notch on W. edges; from which (new bearing trees)

A maple, 12 ins. diam., bears N.53\*E., 7 lks. dist., marked T 28 S R 7 W S 32 B T.

A laurel, 30 ins. diam., bears S.28\*E., 95 lks. dist., marked T 29 S R 7 W S 5 B T.