

County Surveyor's Record, Douglas County, Oregon

5881

Resurvey of portion S.Bdy. T. 28 S., R. 7 W.
(Ford Survey)

CHAINS

A laurel, 16 ins. diam., bears S.4*W., 55 lks. dist.,
marked T 29 S R 7 W S 6 B T.

A fir, 12 ins. diam., bears N.23*W., 79 lks. dist.,
marked T 28 S R 7 W S 31 B T.

Original bearing trees:

A laurel, 20 ins. diam., bears N.30*E., 25 lks. dist.

A fir, 48 ins. diam., bears S.70*E., 18 lks. dist.
(not S.79*E., 75 lks. dist.)

A black oak, 16 ins. diam., bears S.43*W., 43 lks.
dist.

A laurel, 16 ins. diam., bears N.15*W., 100 lks.
dist.

Land, rolling and mountainous.

Soil, clay loam, 1st and 2nd rate.

Timber, fir, oak, laurel, and maple.

Undergrowth, hazel, vinemaple, fir, and oak.

Subdivisions, T 28 S., R. 7 W.

Retracements

From the cor. of secs. 5, 6, 31, and 32, on the S.bdy.
Tp.

North, retracing the line bet. secs. 31 and 32.

18.51 The S. 1/16 sec. cor., bears East, 81 lks. dist.
36.89 The 1/4 sec. cor. bears East, 202 lks. dist.
73.91 Fall 213 lks. W. of the cor. of secs. 29, 30, 31, and 32.

39.96 N.89*30'W., retracing the line bet. secs. 30 and 31.
88.62 The 1/4 sec. cor. bears North, 31 lks. dist.
Fall 126 lks. S. of the cor. of secs. 25, 30, 31, and 36.

39.95 From the cor. of secs. 29, 30, 31, and 32.
79.34 North, retracing the line bet. secs. 29 and 30.
The 1/4 sec. cor. bears East, 50 lks. dist.
Fall 56 lks. W. of the old cor. of secs. 19, 20, 29, and 30.

40.00 N.89*39 1/2'W., retracing the line bet. secs. 19 and 30.
87.32 After careful search, I am unable to find any trace of
the old 1/4 sec. cor. Set temp. cor.
Fall 258 lks. S. of the old cor. of secs. 19, 24, 25,
and 30.