

Subdivisions, T. 28 S., R. 7 W.

CHAINS
28.93

West end of house.

36.80

Old rail fence, bears E. and W.

37.02

Intersect the cor. of secs. 29, 30, 31, and 32, which is a $1\frac{1}{2}$ ins. iron pipe, 1 in. above ground, set by county surveyor; from which the original bearing trees:

A black oak stump, bears N.71*E., 26 lks. dist.,
(not N.73*E., 24 lks.)

A black oak, 40 ins. diam., bears S.30*E., 63 lks. dist.

A black oak, 40 ins. diam., bears S.7*W., 120mlks. dist. (not S.5*W., 168 lks.)

A black oak, 40 ins. diam., bears N.76*W., 28 lks. dist. (not N.80*W., 27 lks.)

New bearing trees:

A white oak, 30 ins. diam., bears N.6*E., 42 lks. dist., marked T 28 S R 7 W S 29 B T.

A black oak, 46 ins. diam., bears S.30*E., 63 lks. dist., marked T.28 S R 7 W S 32 B T.

A pine, 35 ins. diam., bears S.46*W., 93 lks. dist.,
Marked T 28 S R 7 W S 31 B T.

A black oak, 40 ins. diam., bears N.19*W., 17 lks. dist., marked T 28 S R 7 W S 30 B.T.

Land, rolling and level.

Soil, clay loam, 1st and 2nd rate.

Timber, oak, fir, and pine.

Undergrowth, oak, fir, hazel, and laurel.

N.89*03*W., bet. secs. 30 and 31.

Over level open land.

0.36

Road, bears N. and SW.

0.66

Fence, bears N. and W.

10.80

Dry draw, course S.; ascend NE slope, 112 ft. through scattering timber.

26.00

Top of ascent; thence over rolling land.

39.97

Intersect the $\frac{1}{2}$ sec. cor., which is an oak post, set by