

Subdivisions, T. 28 S., R. 7 W.

CHAINS

dist. (not S.78*W.)

A white oak, 20 ins. diam., bears N.38*W., 162 lks.

dist. (not N.40*W., 762 lks.)

New bearing trees:

An ash, 8 ins. diam., bears N.77*E., 18 lks. dist.,
marked T 28 S R 7 W S 4 B T.

A cedar, 10 ins. diam., bears S.77*E., 19 lks. dist.,
marked T 28 S R 7 W S 9 B T.

A fir, 16 ins. diam., bears S.55*W., 34 lks. dist.,
marked T 28 S R 7 W S 8 B T.

A cedar, 10 ins. diam., bears N.62*W., 23 lks. dist.,
marked T 28 S R 7 W S 5 B T.

From this cor., the cor. of secs. 8, 9, 16, and 17, bears
S.0*20' W., 78.00 chs. dist.; a cor. established by
local survey for $\frac{1}{4}$ sec. cor. bet. secs. 8 and 9, bears
S.0*57'W., 38.34 chs. dist.

Land, level and rolling.

Soil, clay loam, 1st and 2nd rate.

Timber, fir, oak, cedar, and pine.

Undergrowth, oak, fir, laurel, and hazel.

N.4*52'W., bet. secs. 4 and 5.

Over rolling land, through heavy timber and dense undergrowth.

Ascend gradual SE. slope, 350 ft.

11.40 Trail, bears NE. and SW.

12.40 Old road, bears NE. and SW.

31.65 Top of ridge, bears E. and SW.; descend NW. slope, 73 ft.

39.47 Apportioned distance.

Set an iron post, 3 ft. long 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S5 $\frac{1}{4}$ S4
1924

from which

A laurel, 20 ins. diam., bears N.70*E., 6 lks. dist.,