

County Surveyor's Record, Douglas County, Oregon

5893

Subdivisions, T. 28 S., R. 7 W.

CHAINS	<p>marked $\frac{1}{4}$ S 4 B T.</p> <p>A laurel, 14 ins. diam., bears N.81*W., 33 lks. dist.,</p> <p>marked $\frac{1}{4}$ S 5 B T.</p> <p>Continue descend, 351 ft.</p> <p>56.25 Top of spur, slopes N.10*W.; descend NE. slope.</p> <p>76.03 Intersect the original S. bdy. of T. 27 S., R. 7 W., at the NE. cor. of sec. 5, T 28 S., R. 7 W., heretofore described.</p> <p>79.33 Intersect the original standard cor. of secs. 4 and 5, established by Ford, restored as NW. cor. of sec. 4, heretofore described.</p> <p>Land, rolling.</p> <p>Soil, clay loam, 2nd rate.</p> <p>Timber, fir, oak, pine, and laurel.</p> <p>Undergrowth, fir, oak, hazel, and laurel.</p>
	<p>From the cor. of secs. 4, 5, 8, and 9,</p> <p>N.89*39*W., bet. secs. 5 and 8.</p> <p>Over rolling land, through heavy timber and dense undergrowth.</p> <p>Ascend over SE. slope, 592 ft.</p> <p>26.40 Old road, bears NE. and SW.</p> <p>34.60 Top of ridge, bears NE. and SW.; descend NW. slope, 43 ft.</p> <p>38.89$\frac{1}{2}$ Apportioned distance.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S5}{S8}$ 1924</p> <p>from which</p> <p>A laurel, 18 ins. diam., bears S.1$\frac{1}{2}$*W., 20 lks. dist.; marked $\frac{1}{4}$ S 8 B T.</p> <p>A fir, 8 ins. diam., bears N.19*W., 41 lks. dist., marked $\frac{1}{4}$ S 5 B T.</p> <p>Descend over NW. slope, 431 ft.</p> <p>52.60 Creek, 2 lks. wide, course N.</p>