

Subdivisions, 28 S., R. 7 W.

CHAINS

S.0\*42'W., bet. secs. 7 and 8.

Over rolling land, through heavy timber and dense undergrowth.

Ascend over NE. slope, 400 ft.

35.05 Top of ridge, bears S. 60\*W. and East.

35.70 Old road along ridge; descend S. slope, 30 ft.

40.08 Intersect the point for  $\frac{1}{4}$  sec. cor., located by record measurement from the original bearing trees, on which the marks are plain.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S7<sup>1</sup>SS  
1924

from which( original bearing trees)

A black oak, 24 ins. diam., bears S.50\*E., 79 lks. dist.

A laurel, 40 ins. diam., bears S.78\*W., 27 lks. dist. (not S.18\*W.)

New bearing trees:

A fir, 16 ins. diam., bears S. 40\*E., 22 lks. dist., marked  $\frac{1}{4}$  S 8 B T.

A fir, 6 ins. diam., bears N.17\*W., 23 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

Land, rolling.

Soil, rocky clay loam, 2nd rate.

Timber, fir, oak, laurel, and maple.

Undergrowth, fir, hazel, laurel, and maple.

From the cor. of secs. 5, 6, 7, and 8.

N.4\*22'W., bet. secs. 5 and 6.

Over rolling land, through heavy timber and dense undergrowth.

Ascend SW. slope, 50 ft.

4.80 Point of spur, slopes NW.; descend NE. slope, 27 ft.