

County Surveyor's Record, Douglas County, Oregon

5905

73

Metes and Bounds
Survey of Tract No. 61, T. 28 S., R. 7 W.

CHAINS

- 18.54 Intersect the N. bdy. of the John Coats D.L.C. No. 59, 6 lks. S.89*30'W. from Cor. No.1 thereof, heretofore described.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for Cor. No. 1 of this Survey, with brass cap marked
- API
TR61
1924
- Thence
West, along the N. bdy. of Tract No. 61.
- 17.25 Wire fence, bears N. and S.; enter grain field.
- 26.30 Board fence, bears N. and S.; leave grain field.
- 28.50 Old rail fence, bears N. and S.; enter field.
- 36.25 Intersect the W. bdy. of original sec. 30, T.28 S., R. 7 W., Ford survey,
- At the point of intersection
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 2 of this survey, with brass cap marked
- AP2
TR61
1924
- Thence
S.1*30'W., along the W. bdy. of original sec. 30, on the W.bdy. of Tract No. 61.
- 0.48 Intersect the S. bdy. of T. 28 S., R. 7½ W., which is at the intersection of the Ford and Hathorn range lines, hereafter described.
- 10.84 NW. cor. of Newland's barn, bears East, 25 lks. dist.
- 11.75 Road, bears NW. and SE.
- 12.90 Road, bears E. and W.
- 13.40 Enter field, bears E. and W.
- 14.00 Intersect Cor. No. 3 of this survey, identical with the original Ford. cor. of secs. 30 and 31, on the W.bdy. of the Tp., hereafter described, and the place of beginning