

Metes and Bounds  
Survey of Tract No. 62, T. 28 S., R. 7 W.

CHAINS

Fractional NW $\frac{1}{4}$ SW $\frac{1}{4}$  of original Sec. 31 by Ford survey.

Note: Preliminary to the survey of Tract No. 62, sec. 31 was subdivided in the field to the extent necessary to determine the position of the 1/16 sec. cors. of the SW $\frac{1}{4}$  of sec. 31 and the corresponding bearing and lengths of the subdivisional lines.

I commence at the Ford original  $\frac{1}{4}$  sec. cor. of sec. 31, on the W. bdy. of the Tp., where I find an iron pipe, 1 in. diam., 3 ins. above ground, set by county surveyor; from which the original bearing tree, now rotted down, a black oak, 22 ins. diam., bears N.24 $\frac{1}{2}$ \*W., 324 lks. dist., blazed plain. SE. bearing tree could not be found. I change this cor. to Cor. No. 2 of this survey, and along side the iron pipe

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for Cor. No. 2 of this survey, with brass cap marked

AP2  
TR62  
1924

Thence

S.1\*28\*W., along the W. bdy. of original sec. 31, and W. bdy. of Tract No. 62.

20.16 Point for S. 1/16 sec. cor., on W. bdy. of original sec. 31.

Set and iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 3 of this survey, identical with Cor. No. 2 of Tract No. 63, with brass cap marked

TR62  
AP3  
AP2  
TR63  
1924

from which

A fir, 10 ins. diam., bears N.18\*E., 28 lks. dist., marked A P 3 TR 62 B T.

A fir, 6 ins. diam., bears S.36\*E., 32 lks. dist., marked A P 2 TR 63 B T.

Thence