

Metes and Bounds  
Survey of Tract No. 62, T. 28 S., R. 7 W.

CHAINS

dist., old marks legible.

Alongside the iron pipe

Set an iron post, 3 ft long, 1 in. diam., 28 ins. in the ground, for cor. No. 3 of this survey, identical with cor. No 2 of Tract No. 47, T. 29 S., R. 7 W., with brass cap marked

TR63  
AP3  
AP2  
TR47  
1924

from which

A fir 26 ins. diam., bears N.30°E., 45 lks. dist., marked AP 3 TR 63 B T.

A fir, 14 ins. diam., bears S. 39°E., 41 lks. dist., marked A P 2 TR 47 B T.

Thence

S.88°52'E., along the original S. bdy. of T 28 S., R. 7 W., bet. Tracts Nos. 63 and 47.

1.46 Intersect the E. bdy. of T. 28 S., 8 W., at the resurvey cor. of Tps. 28 and 29 S., R. 7 W., heretofore described.

2.45 Intersect the W. bdy. of the Wm. McCullough D.L.C. No. 56, 13.55 chs. S.0°30'W, from the NW. cor. No. 2 thereof, heretofore described.

At the point of intersection

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for Cor. No. 4 of this survey, identical with Cor. No. 1 of Tract No. 47, T. 29 S., R. 7 W., with brass cap marked

TR63  
AP4  
AP1  
TR47  
1924

Thence

N.0°30'E., along the E. bdy. of Tract No. 63, on the W. bdy. of the Wm. McCullough D.L.C. No. 56.

13.55 Intersect Cor. No. 5 of this survey, identical with Cor.