

County Surveyor's Record, Douglas County, Oregon

Metes and Bounds
Survey of Tract No. 63, T. 28 S., R. 7 W.

CHAINS

No. 2 of the Wm. McCullough D.L.C. No. 56, heretofore described.

Thence

S.89*44'E., along the S. bdy. of Tract No. 63., on the N. bdy. of the Wm. McCullough D.L.C. No. 56.

22.08 Ten Mile Creek, 30 lks. wide, course S.20*E.

24.18 Intersect the West meridional subdivisional line of sec. 31.

At the point of intersection

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 6 of this survey, with brass cap marked

TR63
AP6

1924

from which

A fir, 10 ins. diam., bears N.20*W., 65 lks. dist., marked A P 6 TR 63 B T.

Thence

N.0*53'E., along the E. bdy. of Tract No. 63, on the W. meridional subdivisional line of original sec. 31.

6.37 Intersect Cor. No. 1 of this survey, and place of beginning.

Resurvey of E. Bdy. T. 28 S., R. 8 W.
(Hathorn Survey)

Retracements

From the original standard cor. of Tps. 28 S., Rs. 7 and 8 W., established by Hathorn, now restored as cor. of Tps. 28 S., Rs. 7½ and 8 W., South retracing the E* bdy. of sec. 1.

30.06 Offset East, 5.55 chs, (record tie). After careful search I am unable to find any trace of the cor. established by Ford for ¼ sec. cor. of secs. 1 and 6.

40.00 Make careful search, find no trace of the Hathorn ¼ sec. cor. of secs. 1 and 6.

68.92 Offset East, 4.55 chs.(record tie). From this point the cor. established by Ford for the cor. of secs. 1, 6, 7, and 12, bears South, 13 lks. and West, 3 lks. dist.

80.08 Fall 16 lks. E. of the cor. of secs. 1, 6, 7, and 12, established by Hathorn.

South, retracing the E. bdy. of sec. 12.

27.24 Offset East, 3.27 chs. (record tie). From this point the cor. established by Ford for ¼ sec. cor. of secs. 7 and