

County Surveyor's Record, Douglas County, Oregon

5911

Resurvey of E. Bdy. T. 28 S., R. 8 W.
(Hathorn Survey)



CHAINS

- 12 bears South, 13 lks. and East 4 lks. dist.
- 40.09 The cor. established by Hathorn for $\frac{1}{4}$ sec. cor. of secs. 7 and 12 bears East 10 lks. dist.
Continue same line and measurement.
- 66.38 Offset East, 3.02 chs. (record tie applied to last cor.).
From this point the cor. established by Ford for cor. of secs. 7, 12, 13, and 18, bears South, 6 lks. and West, 9 lks. dist.
- 80.10 Fall 5 lks. West of the cor. of secs. 7, 12, 13 and 18, established by Hathorn.
-
- South, retracing the E. bdy. of sec. 13.
- 23.40 Offset East, 3.27 Chs. (record tie). From this point the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, established by Ford, bears South, 6 lks. and East 9 lks. dist.
- 39.97 The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, established by Hathorn, bears East, 22 lks. dist.
Continue same line and measurement.
- 61.21 Offset East, 2.27 chs. (record tie applied to last cor.).
From this point the cor. of secs. 13, 18, 19, and 24, established by Ford, bears North, 18 lks. and West 25 lks. dist.
- 79.88 Fall 13 lks. W. of the Cor. of secs. 13, 18, 19, and 24, established by Hathorn.
-
- South, retracing the E. bdy. of sec. 24.
- 19.20 The cor. established by Ford for $\frac{1}{4}$ sec. cor. of secs. 19 and 24 (no tie given), bears East 1.49 chs. dist.
- 39.49 True cor. point for $\frac{1}{4}$ sec. cor. of secs. 19 and 24, established by Hathorn, bears West, 14 lks. dist.
Continue same line and measurement.
- 62.09 Offset East, 1.44 chs. (record tie applied to last cor.).
From this point the cor. of secs. 19, 24, 25, and 30, established by Ford, bears West, 21 lks. dist.
- 79.28 Fall 36 lks. E. of the cor. of secs. 19, 24, 25, and 30, established by Hathorn.
-
- South, retracing the E. bdy. of Sec. 25.
- 16.15 Offset East, 73 lks. (record tie). From this point the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, established by Ford, bears North 12 lks. and West, 15 lks. dist.
- 39.73 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, established by Hathorn, bears West, 37 lks. dist.
Continue same line and measurement.
- 63.14 The cor. of secs. 25, 30, 31, and 36, established by Ford (no tie given) bears West, 65 lks. dist.
- 79.92 Fall 9 lks. E. of the cor. of secs. 25, 30, 31, and 36. established by Hathorn.
-
- South, retracing the E. bdy. of sec. 36.
- 21.65 Offset West, 77 lks. (record tie). From this point the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, established by Ford, bears South, 53 lks. and East, 26 lks. dist.
- 40.10 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, established by Hathorn, bears West, 8 lks. dist.
Continue same line and measurement.
- 62.49 Offset West, 1.35 chs. (record tie applied to last cor.).
From this point the cor. of Tps. 28 and 29 S., Rs. 7 and 8 W., established by Ford, bears West, 19 lks. dist.
- 80.03 Fall 8 lks. E. of the cor. of Tps. 28 and 29 S., Rs. 7 and 8 W., established by Hathorn.

From the cor. of Tps. 28 S., Rs. 7 $\frac{1}{2}$ and 8 W., heretofore described,