

Resurvey of E. Bdy. T. 28 S., R. 8 W.
(Hathorn Survey)

81

CHAINS

brass cap marked

T28S	
R8W	R7½W
S1	S6
S12	S7
1924	

from which

A white fir, 12 ins. diam., bears N.35½°E., 36 lks. dist., marked T.28 S R 7½ W S 6 B T (New B.T.)

A chinquapin, 9 ins. diam., bears S.32°E., 46 lks. dist., marked T 28 S R 7½ W S 7 B T (New B.T.)

A fir, 14 ins. diam., bears S.19°W., (Not S.18°W.), 19 lks. dist.(old bearing tree, marks legible).

A fir, 36 ins. diam., bears N.70°W., 52 lks. dist. (old bearing tree, marks legible).

Land, rolling and mountainous.

Soil, clay loam 2nd rate.

Timber, fir, oak, laurel, and chinquapin.

Undergrowth, hazel, laurel, oak, and fir.

S.0°09'E., along the E. bdy. of sec.12.

Over rolling mountainous land, through heavy timber and dense undergrowth.

Descend over SE. slope, 69 ft.

8.80 Creek, 4 lks. wide, course NE.; ascend 354 ft. on NW. slope.

15.40 Dry draw, course N.30°W.; continue ascent over NE. slope.

22.30 Top of spur, slopes N.30°W.; continue ascent over NW. slope.

33.15 Top of ridge, bears E. and S.60°W.; train along top; descend SE. slope, 135 ft.

40.09 Intersect the point for ¼ sec. cor., located by record measurement from the original bearing trees. Both trees are rotted down, but blazes are plain and stump holes identify their original location.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the