

County Surveyor's Record, Douglas County, Oregon

5915

Resurvey of E. Bdy. T. 28 S., R. 8 W.
(Hathorn Survey)

83
X

CHAINS

from which (new bearing trees)

A fir, 30 ins. diam., bears N.17*E., 59 lks. dist.,
marked T 28 S R 7½ W S 7 B T.

A dogwood, 7 ins. diam., bears S.74*E., 19 lks. dist.,
marked T 28 S R 7½ W S 18 B T.

A fir, 36 ins. diam., bears N.26*W., 52 lks. dist.,
marked T 28 S R 8 W S 12 B T.

Original SW. bearing tree, a fir, 36 ins. diam., bears
S.80*W., 10 lks, dist.

Land, rolling and mountainous.

Soil, clay loam, 2 nd rate.

Timber, fir, oak, and laurel.

Undergrowth, hazel, laurel, oak, and fir.

S.0*19'E., along the E. bdy. of sec. 13.

Over mountainous land, through heavy timber and dense
undergrowth.

Ascend NE. slope, 148 ft.

4.45 Top of spur, slope E.; descend SE. slope 212.ft.

14.58 Draw, course E.; ascend N. slope, 285 ft.

17.40 Draw, course NE.

26.65 Top of spur, slopes N.70*E.; descend SE. slope, 382 ft.

39.97 Intersect the point for ¼ sec. cor., located by measure-
ment from the original bearing trees. The blazes are
plain but marks are grown over.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for ¼ sec. cor., with brass cap marked

S13 | S18
 | R7½
 1924

from which (original bearing trees)

A fir, 24 ins. diam., bears N.63*E., 9 lks. dist.,
re-marked ¼ S 18 R 7½ B T.

A fir, 10 ins. diam., bears N.31*W.(not N.34*W.),
40 lks. dist., re-marked ¼ S 13 B T.