

County Surveyor's Record, Douglas County, Oregon

Resurvey of E. Bdy. T. 28 S., R. 8 W.
(Hathorn Survey)

CHAINS

undergrowth.

Descend over SE. slope, 317 ft.

29.15 Draw, course SW.; ascend along W. slope, 51 ft.

33.85 Top of spur, slopes SW.; descend SE. slope, 44 ft.

39.22 Old fence, bears E. and W.

39.73 Intersect the point for $\frac{1}{4}$ sec. cor., located by record measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S25 S30
 | R7 $\frac{1}{2}$
 1924

from which

A black oak, 10 ins. diam., bears N.31 $\frac{1}{2}$ *E., 102 lks. dist., marked $\frac{1}{4}$ S 30 BT (by county survey).

A black oak, 18 ins. diam., bears N.81 $\frac{1}{2}$ *W., 111 lks. dist., marked $\frac{1}{4}$ S 25 B T (by county survey).

I mark

A black oak, 10 ins. diam., bears N.13*E., 50 lks. dist., marked $\frac{1}{4}$ S 30 R 7 $\frac{1}{2}$ B T.

Original bearing tree, a black oak stump, bears N.35*W., 164 lks. dist.

Original bearing tree, a black oak stump, bears N.30*E. (not N.23*E.), 207 lks. dist.

From this cor. the NE. cor. of the A.E.Lathrop D.L.C.

No. 37 bears S.35*15*W., 12.56 chs. dist.

Thence from the $\frac{1}{4}$ sec cor.

S.0*24*E., along the E. bdy. of sec. 25.

descend gradual SE. slope, 145 ft. to sec. cor.

2.45 Enter grain field, bears NE. and W.

9.89 Intersect the range line bet. Tps. 28 S., Rs. 7 and 8 W., as established by Ford, at 13.53 chs. N.1*30*E. from Ford's cor. of secs. 25, 30, 31, and 36, hereafter described.

At the point of intersection