

County Surveyor's Record, Douglas County, Oregon

5921

89 X

Resurvey of E. Bdy. T. 28 S., R. 8 W.

(Hathorn Survey)

CHAINS

"I determined the position of the true corner by tie given in the Govt. field notes of the Lathrop D.L.C., and also by one old bearing tree, which was lying down, and Mr. W.H.coats testified that he had seen it cut open and the scribe marks bared by a previous surveyor, and pointed out its original position to me."

From the true cor, point the witness cor. to the cor. of secs. 25 and 36, established by the county surveyor, bears West, 38 lks. dist. This cor. is an iron pipe, 1 in. diam., 4 ins. above ground; from which (county survey bearing trees)

A naple, 16 ins. diam., bears N.22*E., 18 lks. dist., marked C S T 28 S R 7 W S 31 B T.

An alder, 12 ins. diam., Bears S.35*W., 37 lks. dist., marked C S T 28 S R 8 W S 36 B T.

An ash, 24 ins. diam., bears N.27*W., 44 lks. dist., marked C S T 28 S R 8 W S 25 B T.

Alongside the iron pipe

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins, in the ground, for witness cor. to the cor. of secs. 25 and 36, with brass cap marked

T28S;
S25|WC

S36|
R8W|
1924

and add the marks W C to the bearing trees in secs. 25 and 36.

Land, mountainous and rolling prairie.

Soil, clay loam, 1st and 2nd rate.

Timber, oak, fir, alder, maple, and ash.

Undergrowth, oak, fir, and alder.

S.0*07'W., from true cor. point, along the E. bdy. of sec. 36.

Over level land, through scattering timber and dense undergrowth.

0.50 Leave bed of Ten Mile Creek, course NE.

2.00 Leave timber and brush, bears NW. and SE.