

Resurvey of E. Bdy. T. 28 S., R. 8 W.  
(Hathorn Survey)

CHAINS

- 3.65 Wire fence, bears NW. and SE.; enter grain field.
- 9.21 Intersect S. bdy. of Tract No. 61, East 51 lks. from the SW. cor. No.4 thereof, heretofore described.
- 10.96 Intersect S. bdy. of the John Coats D.L.C. No. 59. The "L" cor. No. 4 thereof, heretofore described, bears N.89\*14'E., 13 lks. dist., and the SW.cor., heretofore described, bears S.89\*14'W., 7.37 chs. dist.
- 10.98 Board fence, bears E. and W. 30 lks., then angles S.; leave grain field; enter scattering timber.
- 20.26 Board fence, bears E. and W.
- 22.18 Intersect center latitudinal subdivision line of sec. 31, T. 28 S., R. 7 W., S.89\*53'E., 46 lks. from Ford's original 1/4 sec. cor., heretofore described.

At the point of intersection

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for resurvey 1/4 sec. cor. of sec. 31, T. 28 S., R. 7 W., with brass cap marked

1/4 S31  
1924

from which

A Chittem, 6 ins. diam., bears N.47\*E., 65 lks. dist., marked 1/4 S. 31 B T.

No other bearing trees available.

- 29.50 Leave scattering timber; enter heavy timber, bears E. and W.
- 30.00 Old road, bears E. and W.
- 31.08 The S. SW. cor. No 5 of the John Coats D.L.C. No.59, bears East, 3 lks. dist., heretofore described.
- 31.20 Stream, 3 lks. wide, course E.; ascend gradual N. slope, 75 ft.
- 40.10 Intersect the point for 1/4 sec. cor., located by record bearing and distance from the original NW. bearing tree; marks are plain on the bark. The SE. bearing tree is not found.

At the exact cor. point.