

County Surveyor's Record, Douglas County, Oregon

5923

Resurvey of E. Bdy. T 28 S., R. 8 W.
(Hathorn Survey)



CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap marked

$\frac{1}{4}$
S36
1924

from which (new bearing trees)

A fir, 16 ins. diam., bears S.37*W., 42 lks. dist., marked $\frac{1}{4}$ S 36 B T.

Original NW. bearing tree, a fir, 36 ins. diam., bears N.87*W., 32 lks. dist., marked $\frac{1}{4}$ S B T.

Thence from the $\frac{1}{4}$ sec. cor.

South, along the E. bdy. of sec. 36.

Ascend NE. slope, 84 ft. along old fence line.

2.25 Intersect the line bet. Tracts Nos. 62 and 63, S.89*22'E., 95 lks. from the S. 1/16 sec. cor. of sec. 31 of the Ford survey.

3.20 Top of spur, slopes SE.; descend SW. slope, 75 ft.

8.82 NW. cor. of Wm. McCullough D.L.C. No. 56, bears East, 1.11 chs. dist., heretofore described.

8.96 Board fence, bears East.

17.65 Bottom of descent; ascend NE. slope, 130 ft.

18.65 Enter heavy timber, bears E. and W.

22.42 Intersect the S. bdy. of sec. 31, S.88*52'E., 1.46 chs. from Ford's cor. of Tps. 28 and 29 S., Rs. 7 and 8 W., heretofore described.

At the point of intersection

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for resurvey cor. of Tps. 28 and 29 S., R. 7 W., with brass cap marked

T28S
R7W
S31
S6
T29S
1924

from which

A fir, 6 ins. diam., bears N.81*E., 62 lks. dist., marked T 28 S R 7 W S 31 B T.