

County Surveyor's Record, Douglas County, Oregon

Resurvey of E. Bdy. T. 28 S., R. 8 W.
(Hathorn Survey)

X

CHAINS

A fir, 10 ins. diam.; bears S.80 $\frac{1}{2}$ *E., 58 lks.dist.,
marked T 29 S R 7 W S 6 B T.

26.50 Top of spur, slopes SE.; leave heavy timber, bears NW.
and SE.; descend S. slope, 94 ft.


31.30³⁰ Head of draw, course SE. $\frac{1}{2}$ ascend 30 ft.

33.10 Top of ascent; descend SE. slope, 87 ft.

39.93 Intersect the point for cor. of Tps. 28 and 29 S., Rs. 7
and 8 W., established by Hathorn, located by bearing
and measurement from the original NE. and NW. bearing
trees, on which the marks are legible. The original
SE. and SW. bearing trees are not found.

At the exact cor. point

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in
the ground, for cor. of Tps. 28 and 29 S., R.8 W.,
with brass cap marked



from which (new bearing trees)

A white oak, 12 ins. diam., bears S.5 $\frac{1}{2}$ *W., 168 lks.
dist., marked T 29 S R 8 W S 1 B T.

A white oak, 7 ins. diam., bears N.21 $\frac{3}{4}$ *W., 166 lks.
dist., marked T 28 S R 8 W S 36 B T.

Original NE. bearing tree, a white oak, 20 ins.diam.,
bears N.0*30'E., 256 lks. dist.

Original NW. bearing tree, a black oak, 24 ins. diam.,
bears N.5*W., 335 lks. dist.

Land, rolling.

Soil, clay loam, 1st and 2 nd rate.

Timber, fir, and oak,

Undergrowth, fir, oak, and hazel.