

County Surveyor's Record, Douglas County, Oregon

5925

Resurvey of W. Bdy. T. 28 S., R. 7 W.
(Ford Survey)

93

CHAINS

From the standard NW. cor. of T. 28 S., R. 7 W., heretofore described.

S.0*41'W., along the W. bdy. of sec. 6.

Over level open land, through oak openings.

2.75 Creek, 4 lks. wide, course SE.

8.70 Fence, bears E. and W.

8.78 Intersect the NE. cor. of T. 28 S., R. 7½ W., heretofore described.

10.25 Ascend NE. slope, 93 ft.

19.35 Top of ridge, bears NW. and SE.; descend along E. side of spur, 178 ft.

27.70 Top of spur, slopes SE.; descend S. slope.

33.45 Road, bears E. and W.

36.70 Looking Glass Creek. 25 lks. wide, course E.; ascend N. slope, 32 ft.

38.86 Point for ¼ sec. cor., located by Hathorn's record tie for the Hathorn ¼ sec. cor. of secs. 1 and 6, heretofore described.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 6 only, with brass cap marked

¼ S 6
1924

from which

A fir, 18 ins. diam., bears N.23*E., 46 lks. dist., marked ¼ S 6 B T.

A fir, 14 ins. diam., bears S.36*E., 37 lks. dist., marked ¼ S 6 B T.

Thence from the ¼ sec. cor..

S.1*19'W., along the W. bdy. of sec. 6.

Ascend N. slope, 198 ft. to spur.

9.94 To a point 5.28 chs. East of Hathorn's ¼ sec. cor. of Secs. 1 and 6, on the E. bdy. of T. 28 S., R. 8 W., heretofore described.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the