

County Surveyor's Record, Douglas County, Oregon

5929

Resurvey of W. Bdy. T. 28 S., R. 7 W.
(Ford Survey)

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A maple, 12 ins. diam., bears N.62*E., 66 lks. dist., marked T 28 S R 7 W S 7 B T.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S.81*E., 54 lks. dist., marked T 28 S R 7 W S 18 B T.</p> <p>Original SE. bearing tree, a fir, 36 ins. diam., bears S.50*E., 32 lks. dist.</p> <p>Original SW. bearing tree, a fir, 36 ins. diam., bears S.25*W., 38 lks. dist.</p> <p>Original NE. bearing tree, a fir, 36 ins. diam., bears N.12½*E., 164 lks. dist. (not N.12*E., 200 lks.)</p> <p>Land, rolling.</p> <p>Soil, clay loam, 2nd rate.</p> <p>Timber, oak, fir, pine, and cedar.</p> <p>Undergrowth, oak, fir, laurel, and hazel.</p>
	<p>S.0*54'E., along the W. bdy. of sec. 18.</p> <p>Over mountainous land, through scattering timber and undergrowth.</p>
0.15	Draw, course E.; ascend N. slope, 123 ft.
4.40	Top of spur, slopes N.60*E.; descend SE. slope, 90 ft.
10.40	Draw, course NE.; ascend NE. slope, 231 ft.
13.67	Intersect the cor. of secs. 7 and 18, T. 28 S., R. 7½ W., hereafter described.
18.05	Top of spur, slopes, E.; descend SE. slope, 180 ft.
27.75	Dry draw, course N.60*E.; ascend NE. slope, 285 ft.
37.14	Intersect the point for ¼ sec. cor., established by Ford, located by record measurement from the original bearing trees, upon which the marks are legible.
	<p>At the exact cor. point</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 18 only, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0;"> 1" S 18 1924</p> </div> <p>from which (new bearing trees)</p>