

Resurvey of W. Bdy. T. 28 S., R. 7 W.
(Ford Survey)

CHAINS

A fir, 6 ins. diam., bears N.57*E., 9 lks. dist.,
marked $\frac{1}{2}$ S 18 B T..

A fir, 4 ins. diam., bears S.8*E., 4 lks. dist.,
marked $\frac{1}{2}$ S 18 B T.

Original NE. bearing tree, a black oak (dead), bears N.65*
E., 37 lks. dist.

Original NE. bearing tree, a black oak, bears N.73 *W.
(not N.75*W.), 28 lks. dist.

Thence from the $\frac{1}{2}$ sec. cor.

S.2*12*W., along the W. bdy. of sec. 18.

Ascend NE. slope 41ft.

2.50 Top of spur, slopes E.; descend SE. slope, 409 ft.

10.95 Top of spur, slopes SE.; descend S. and SW. slope.

16.53 To a point 2.61 chs. E. of Hathorn's $\frac{1}{2}$ sec. cor. of secs.
13 and 18, on E. bdy. of T. 28 S., R. 8 W., heretofore
described.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{2}$ sec. cor. of sec. 18 only, T.28 S., R.
7 $\frac{1}{2}$ W., with brass cap marked

$\frac{1}{2}$ S18
R7 $\frac{1}{2}$
1924

from which

A fir, 18 ins. diam., bears S.68*W., 51 lks. dist.,
marked $\frac{1}{2}$ S 18 R 7 $\frac{1}{2}$ B T.

A cedar, 40 ins. diam., bears N.56*W., 40 lks. dist.,
marked $\frac{1}{2}$ S 18 R 7 $\frac{1}{2}$ B T.

18.45 Stream, 3 lks. wide, course S.60*E.; ascend N. slope, 77
ft.

22.40 Top of spur, slopes NE.; descend 12 ft.

29.70 Draw, course NE.; ascend NW. slope, 281 ft.

37.60 Intersect the point for cor. of secs. 13, 18, 19, and 24,
established by Ford, located by record measurement from
the original NE. and SE. bearing trees, upon which the
marks are still legible. The SW. and NW. bearing trees
have rotted away.