

County Surveyor's Record, Douglas County, Oregon

Resurvey of W. Bdy. T. 28 S., R. 7 W.
(Ford Survey)

99

CHAINS

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 18 and 19 only, with brass cap marked

T28S
S18
S19
R7W
1924

from which

A fir, 30 ins. diam., bears N.53*E., 21 lks. dist., marked T 28 S R 7 W S 18 B T.

A fir, 12 ins. diam., bears S.9*E., 20 lks. dist., marked T. 28 S R 7 W S 19 B T.

Original NE. bearing tree, a maple, 6 ins. diam., bears N.15*E., 15 lks. dist.

Original SE. bearing tree, a fir, 24 ins. diam., bears S.88*E. (not S.83*E.), 12 lks. dist.

Land, mountainous.

Soil, clay loam, 2nd and 3rd rate.

Timber, fir, oak, and cedar.

Undergrowth, fir, oak, hazel, and laurel.

S.0*36'W., along the W. bdy. of sec. 19.

Over Mountainous land, through scattering timber and undergrowth.

Ascend N. slope, 132 ft.

4.00 Top of ridge, bears E. and W.; descend S. slope, 40 ft.

17.15 Draw, course NW.; ascend NE. slope, 34 ft.

18.85 Intersect the cor. of secs. 18 and 19, T. 28 S., R. 7½ W. hereafter described.

Ascend NW. slope, 145 ft.

26.95 Top of spur, slopes, SW.; descend SE. slope, 242 ft.

38.05 Intersect the point for ¼ sec. cor., established by Ford, located by record measurements from the original bearing trees. The blazes are plain, marks grown over and not opened.