

Resurvey of W. Bdy. T. 28 S., R. 7 W.
(Ford Survey)

CHAINS

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 19 only, with brass cap marked

| $\frac{1}{4}$ S19
1924

from which

A white oak, 8 ins. diam., bears N.68*E., 85 lks. dist., marked $\frac{1}{4}$ S 19 B T.

Original bearing tree, a white oak, 30 ins. diam., bears S.89*E. (not N.85*E.), 60 lks. dist.

Original bearing tree, a white oak, 30 ins. diam., bears N.10*W., 100 lks, dist.

Thence from the $\frac{1}{4}$ sec. cor.

S.0*22'W., along the W. bdy. of sec. 19.

Continue descent, 425 ft.

12.94 Rocky draw, course SW.; ascend NW. slope, 46 ft.

17.50 Top of rocky spur, slopes SW.; descend S. slope, 74 ft.

20.28 To a point 1.50 chs. East of Hathorn's $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on E. bdy. of T. 28 S., R. 8 W., heretofore described.

Point for $\frac{1}{4}$ sec. cor. falls on surface bedrock, impracticable to set iron post; therefore, at the exact cor. point I mark a cross (x) on the bedrock, over which set a basalt stone, 20x10x4 ins., in mound of stone and earth, for $\frac{1}{4}$ sec. cor. of sec. 19 only, T. 28 S., R. 7 $\frac{1}{2}$ W., marked $\frac{1}{4}$ on W. face; from which

A black oak, 5 ins. diam., bears N.32*W., 81 lks. dist., marked $\frac{1}{4}$ S 19 R 7 $\frac{1}{2}$ B T.

A fir, 10 ins. diam., bears S.7 $\frac{1}{2}$ *W., 130 lks. dist., marked $\frac{1}{4}$ S 19 R 7 $\frac{1}{2}$ B T.

22.10 Draw, course NW.; ascend 25 ft.

23.33 Point of Spur, slopes W.; descend SW. slope, 60 ft.

28.87 Draw, course NW.; ascend 245 ft.

42.89 Intersect the point for cor. of secs. 19, 24, 25, and 30,