

Resurvey of W. Bdy. T. 28 S., R. 7 W.
(Ford Survey)

CHAINS

Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 30 Only, with brass cap marked.

$\frac{1}{4}$ S30
1924

from which (new bearing trees)

A fir, 24 ins. diam., bears N.28*E., 18 lks. dist., marked $\frac{1}{4}$ S 30 B T.

A fir, 26 ins. diam., bears S.44*E., 42 lks. dist., marked $\frac{1}{4}$ S 30 B T.

Original bearing tree, a black oak, 20 ins. diam., bears S.27*E., 56 lks. dist.

Original bearing tree, a black oak, 24 ins. diam., bears N.3 $\frac{1}{2}$ *W., 122 lks. dist.

County survey cor. bears South, 7 lks. and West, 3 lks. dist.

Thence from the $\frac{1}{4}$ sec. cor.

S.1*30*W., along the W. bdy. of sec. 30.

Descend SE. slope, 119 ft.

12.15 Draw, course SW.; ascend along W. slope, 42 ft.

19.80 Top of spur, slopes SW.; descend SE. slope, 39 ft.

23.27 Old fence, bears E. and W.

23.71 To a point 0.33 chs. East of Hathorn's $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on E. bdy. of T. 28 S., R. 8 W., heretofore described.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 30 only, T. 28 S., R. 7 $\frac{1}{2}$ W., with brass cap marked

$\frac{1}{4}$ S30:
R7 $\frac{1}{2}$:
1924

from which

A black oak, 16 ins. diam., bears N.24*W., 54 lks. dist., marked $\frac{1}{4}$ S 30 R 7 $\frac{1}{2}$ B T.

No other tree in sec. 30 available, no stones available for mound.

33.12 Point for cor. No 2, Tract No. 61, heretofore described, erroneously shown on plat approved March 30, 1863, as