

Resurvey of W. Bdy. T. 28 S., R. 7 W.  
(Ford Survey)

CHAINS

NW. cor. of the John Coats D.L.C. No. 59.

33.60 Intersect the E. bdy. of T. 28 S., R. 8 W., at the S. cor. of T. 28 S., R. 7½ W., heretofore described.

47.12 Intersect the cor. of secs. 25, 30, 31, and 36, established by Ford, which is an iron pipe, 2 ins. diam., 3 ins. above ground, set by county surveyor and located by him from an Oak stump, 30 ins. diam., no marks visible, bearing N.85°E., 10.17 chs. dist. Statements of old residents indicate this stump to have been original bearing tree and it is so accepted by the county surveyor. I accept his findings, having no better evidence of the original position of the cor.

This cor. now becomes Angle point No. 3 of Tract 61.

The resurvey cor. of secs. 30 and 31, heretofore described, bears S.88°23'E., 45 lks. dist.

Subdivisions, T. 28 S., R. 7½ W.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of T. 28 S., R. 8 W.

East, bet. secs. 19 and 30.

Over rolling land, through heavy timber and dense undergrowth.

1.06 Intersect the W. bdy. of T. 28 S., R. 7 W., 17.20 chs. S.1°42'W. from the cor. of secs. 19 and 30.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19 and 30, with brass cap marked

T28S;  
S19  
S30  
R7½W  
1924

from which

A fir, 12 ins. diam., bears S.70°W., 16 lks. dist., marked T 28 S R 7½ W S 30 B T.

A fir, 20 ins. diam., bears N.57°W., 27 lks. dist.,