

County Surveyor's Record, Douglas County, Oregon

5937

Subdivisions, T. 28 S., R. 7½ W.

CHAINS
3.11

Intersect the W. bdy. of T. 28 S., R. 7 W., 13.67 chs.
S.0°54'E. from the cor. of secs. 7 and 18.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 7 and 18, with brass cap
marked

T28S:
S7:
S18:
R7½W:
1924

from which

A black oak, 12 ins. diam., bears S.68°W., 54 lks.
dist., marked T. 28 S R 7½ W S 18 B T.

A fir, 20 ins. diam., bears N.13°W., 18 lks. dist.,
marked T 28 S R 7½ W S 7 B T.

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, fir, oak, and laurel.

Undergrowth, hazel, fir, and laurel.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy.
of T. 28 S., R. 8 W.

East, bet. secs. 6 and 7.

Over rolling land, through heavy timber and dense under-
growth.

Descend E. slope, 32 ft.

4.28 Intersect the W. bdy. of T.28 S., R. 7 W., 11.04 chs.
S.2°03'W. from the cor. of secs. 6 and 7.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 6 and 7, with brass cap
marked

T28S:
S6:
S7:
R7½W:
1924

from which