

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 28 S., R. 7 1/2 W.

CHAINS

A laurel, 20 ins. diam., bears S.53\*W., 20 lks.dist., marked T. 28 S R 7 1/2 W S 7 B T.

A fir, 12 ins. diam. bears N.31\*W., 43 lks. dist., marked T 28 S R 7 1/2 W S 6 B T.

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, fir, oak, and laurel.

Undergrowth, hazel, fir, oak, and laurel.

Final Test of Instrument.

Sept. 20, 1924: On the meridian determined by observation on Polaris, May 7, 1924, I set off 43\*09' on the lat. arc; 0\*57'N. on the decl. arc; and at 3h 0m P.M., app.t., determine a meridian with the solar, which coincides with the true meridian determined by Polaris observation.

West Bdy. T. 29 S., R. 7 W.  
(Ford Survey)

I commence at cor. No. 3 of Tract No. 48, on the W.bdy. of original sec. 6, T.29 S., R. 7 W.

Thence

S.0\*07'E., on a blank line, along the W. bdy. of original sec. 6.

39.60

Intersect the point for Ford's cor. of secs. 1, 6, 7, and 12, restored by Hathorn's record tie.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins, in the ground, for witness point, with brass cap marked

WP  
1924

from which

A white oak, 32 ins. diam., bears N.55\*E., 136 lks. dist., marked W P B T.

A white oak, 18 ins. diam., bears S.21\*E., 167 lks. dist., marked W P B T.

Thence