

County Surveyor's Record, Douglas County, Oregon

5939  
785  
X

West Bdy. T. 28 S., R. 7 W.  
(Ford Survey)

CHAINS

S.0°28'W., on a blank line, along the W. bdy. of original sec. 7.

29.46 Intersect the point for Ford's  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, located by record bearing and distance from the original NE. bearing tree.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness point, with brass cap marked

WP  
1924

from which (the original bearing tree)

A black oak, 24 ins. diam., bears N.16°E., 38 lks. dist., marks grown over, not opened, blazes show plainly,

New bearing trees:

A fir, 20 ins. diam., bears N.65°E., 34 lks. dist., marked W P B T.

A fir, 10 ins. diam., bears S.44 $\frac{1}{2}$ °E., 19 lks. dist., marked W P B T.

Thence

S.1°45'W., on a blank line, along the W. bdy. of original sec. 7.

38.43 Intersect cor. No. 2, Tract No. 49, identical with the Ford cor. of secs. 7, 12, 13, and 18, hereafter described.

I now go to cor. No. 3, Tract No. 52, identical with the Ford cor. of secs. 13, 18, 19, and 24, hereafter described.

Thence

S.0°57'E., on a blank line, along the W. bdy. of original sec. 19.

37.94 Intersect the point for Ford's  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, located by measurement from the original bearing trees.

At the exact cor. point