

Subdivisions, T. 29 S., R. 7 W.

CHAINS S.0*30'E., bet. secs. 5 and 6.
 Ascend over NW. slope, 401 ft.
 20.10 Woven wire fence, bears East.
 22.30 Top of spur, slopes SW.; descend SE. slope, 351 ft.
 40.10 Intersect the point for cor. of secs. 5, 6, 7, and 8 located by measurement from the original bearing trees.
 At the exact cor. point
 Set an iron post, 3 ft. long, 2 ins. diam., 28ins. in the ground, for cor. of secs. 5, 6, 7, and 8, with brass cap marked

T29S:R7W
 S6:S5
 S7:S8
 1924

from which (old bearing trees)

A black oak, 36 ins. diam., bears N.40*E., 98 lks. dist. (not 100 lks.)

A black oak, 40 ins. diam., bears S.31½*E., 103 lks. dist. (not S.34*E., 104 lks.)

A white oak, 44 ins. diam., bears S.65*W., 67 lks. dist. (not 69 lks.)

A black oak, 46 ins. diam., bears N.40*W., 177 lks. dist. (not N.39*W., 179 lks.)

Marks are legible on all these trees.

New bearing trees:

A laurel, 12 ins. diam., bears N.7*E., 54 lks. dist., marked T 29 S R 7 W S 5 B T.

A black oak, 14 ins. diam., bears S.72*E., 8 lks. dist., marked T 29 S R 7 W S 8 B T.

A white oak, 12 in. diam., bears S.20*W., 2½ lks. dist., marked T 29 S R 7 W S 7 B T.

A fir, 12 ins. diam., bears N.29*W., 63 lks. dist., marked T 29 S R 7 W S 6 B T.

Land, mountainous.

Soil, clay loam, 2nd rate.

Timber, oak, fir, and laurel.

Undergrowth, hazel, fir, and laurel.