

Subdivisions, T. 29 S., R. 7 W.

CHAINS

79.00

Intersect the point for cor. of secs. 7, 8, 17, and 18,  
located by measurement from the original bearing trees.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground, for cor. of secs. 7, 8, 17, and 18, with  
brass cap marked

T29S:R7W  
S7:S8  

---

S18:S17  
1924

from which (the original bearing trees)

A black oak, 18 ins. diam., bears N.44 $\frac{1}{2}$ \*E., 72 lks.  
dist., (not N.43 $\frac{1}{2}$ \*E.), blazes are plain.

A black oak, 24 ins. diam., bears S.69 $\frac{1}{2}$ \*E., 59 lks.  
dist. (not S.72\*E.), blazes and marks plain.

A black oak, 16 ins. diam., bears S.66\*W., 68 lks.  
dist. blazes plain.

A black oak, 40 ins. diam., bears N.42\*W., 8 lks.  
dist., marks are plain.

New bearing trees:

A fir, 14 ins. diam., bears N.29\*E., 52 lks. dist.,  
marked T 29 S R 7 W S 8 B T.

A fir, 10 ins. diam., bears S.88 $\frac{1}{2}$ \*E., 72 lks. dist.,  
marked T 29 S R 7 W S 17 B T.

A fir, 30 ins. diam., bears S.67\*W., 40 lks. dist.,  
marked T 29 S R 7 W S 18 B T.

A black oak, 30 ins. diam., bears N.24\*W., 42 lks.  
dist., marked T 29 S R 7 W S 7 B T.

Land, rolling and level.

Soil, clay loam, 1st and 2nd rate.

Timber, oak and fir.

Undergrowth, hazel, oak, and fir.

N.89\*18\*W., bet. secs. 7 and 18.

Over rolling land, through scattering timber and dense  
undergrowth.

Ascend NE. slope, 90 ft.