

CHAINS  
10.35

Top of low ridge, bears N.70\*W. and S.70\*E.; ascend gradually along S. slope, 111 ft.

19.65 Top of ridge, bears NE. and SW.; descend gradually 43 ft.

22.35 Head of Draw, course N.; ascend NE. slope, 392 ft.

30.05 Wire fence, bears N. and S.

39.19 Intersect the point for 1/4 sec. cor., located by record bearing and distance from the original NE. bearing tree.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S7  
S18  
1924

from which ( the old bearing trees)

A black oak, 40 ins. diam., bears N.40\*E., 29 lks. dist., blazes plain, marks grown over and not opened.

The SE. black oak tree is rotted down.

New bearing trees:

A fir, 18 ins. diam., bears S.43\*E., 45 lks. dist., marked 1/4 S18 B T.

A fir, 16 ins. diam., bears N.8\*W., 66 lks. dist., marked 1/4 S 7 B T.

Thence from the 1/4 sec. cor.

N.76\*03'W., bet. secs. 7 and 18.

Ascend NE. slope, 40 ft.

2.00 Top of ridge, bears N.70\*W. and S.70\*E.; descend 140 ft.

16.30 Top of flat spur, slopes SE.; descend S. slope.

22.78 Point for W. 1/16 sec. cor. bet. secs. 7 and 18, and cor. No. 1 of Tract No. 49.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No.1 of Tract No. 49, with brass cap marked

S7  
W 1/16  
API:S18  
TR 49:  
1924

from which

A fir, 7 ins. diam., bears S.44\*W., 39 lks. dist.,