

County Surveyor's Record, Douglas County, Oregon

5951
119

Subdivisions, T 29 S., R.7 W.

CHAINS

Land, rolling.

Soil, rocky clay loam, 2nd rate.

Timber, fir, oak, cedar, and maple.

Undergrowth, Vinemaple, fir, hazel, oak and snowbrush.

N.89°22'W., bet. secs. 18 and 19.

Over rolling land, through heavy timber and dense undergrowth.

Ascend SE. slope, 245 ft.

9.00 Top of spur, slopes NE.; descend along N. slope, 112 ft.

13.35 Head of draw, course N.; ascend NE. slope, 95 ft.

17.60 Top of spur, slopes N.; descend NW. slope, 303 ft.

31.60 Draw, course N.; ascend NE. slope, 71 ft.

38.37 Intersect the point for $\frac{1}{4}$ sec. cor., located by record bearing and measurement from the N.E. bearing tree.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S18}{S19}$$

1924

from which (the original bearing tree)

A laurel snag, bears N.58°E., 15 lks. dist., old blazes show.

New bearing trees:

A chinquapin, 12 ins. diam., bears N.53°E., 49 lks. dist., marked $\frac{1}{4}$ S 18 B T.

A laurel, 10 ins. diam., bears S.21°E., 14 lks. dist., marked $\frac{1}{4}$ S 19 B T.

Thence from the $\frac{1}{4}$ sec. cor.

N.75°02'W., bet. secs. 18 and 19.

0.25 Spur, slopes NW.; descend SW. slope, 100 ft.

4.25 Draw, course NW.

9.60 Draw, course N.; continue descent along N. slope, 125 ft.

18.85 Draw, course N.

20.65 Draw, course N.; ascend NE. slope, 45 ft.

22.73 Point for W. $\frac{1}{16}$ sec. cor. bet. secs. 18 and 19, identical with cor. No. 4 of Tract No. 52.