

Subdivisions, T. 29 S., R. 7 W.

CHAINS

Set an iron post 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 4 of Tract No. 52, with brass cap marked

TR 52:
 $\frac{AP\ 4:S18}{S19}$ W 1/16
 1924

from which

A white oak, 10 ins. diam., bears N.44*W., 42 lks. dist., marked A P 4 TR 52 B T.

- 24.95 Point of spur, slopes N.; descend NW. slope 143 ft.
- 31.60 Olalla Creek, 20 lks. wide, course N.60*E.; ascend gradually 40 ft.
- 40.75 Same creek, 20 lks. wide, course SE.; ascend NE. slope, 37 ft.
- 45.54 Intersect the W. bdy. of the Tp., at the resurvey cor. of secs. 18 and 19.
- Original Ford cor. of secs. 13, 18, 19, and 24, bears N.75*02'W., 2.97 chs. dist.
- Land, rolling.
- Soil, clay loam, 2nd rate.
- Timber, fir, oak, laurel, and chinquapin.
- Undergrowth, hazel, fir, laurel, and oak.
-
- From the cor. of secs. 17, 18, 19, and 20.
- S.1*23'W., bet. secs. 19 and 20.
- Over rolling land, through heavy timber and dense undergrowth.
- Ascend NE. slope, 168 ft.
- 10.07 Top of spur, slopes E.; descend SW. slope, 500 ft.
- 33.00 Draw, course SE.; continue descent over SE. slope.
- 38.84 Intersect the point for $\frac{1}{2}$ sec. cor., located by measurement from the original bearing trees.
- At the exact cor. point
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{2}$ sec. cor., with brass cap marked
- $\frac{1}{2}$
 S19:S20
 1924
- from which (the original bearing trees)
- A fir, 16 ins. diam., bears S.77*E., 11 lks. dist.