

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 29 S., R. 7 W.

5955

173

7

CHAINS

N.80\*27' W., 2.24 chs. dist.

Land, rolling and mountainous.

Soil, clay loam, 2nd rate.

Timber, fir, oak, cedar, and laurel.

Undergrowth, oak, hazel, snowbrush, and fir.

From the cor. of secs. 19, 20, 29, and 30.

bet  
S.0\*55'W., /secs. 29 and 30.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend NW. slope, 405 ft.

9.50 Perpendicular cliff 50 ft. high, bears NE. and SW.

24.10 Top of ridge, bears N.20\*E. and S.20\*W.; continue ascent along E. slope.

29.45 Top of spur, slopes SE.; descend SW. slope 82 ft.

38.67 Intersect the point for  $\frac{1}{4}$  sec. cor., located by measurement from the original bearing trees.

At the exact cor. point,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S30:S29  
1924

from which (the original bearing trees)

A black oak, 30 ins. diam., bears N.82 $\frac{1}{2}$ \*E., 109 lks. dist. (not N.87 $\frac{1}{2}$ \*E.), marks grown o ver.

A pine stump, 40 ins. diam., bears S.60\*W., 69 lks. dist. (not S.61\*W.)

New bearing trees:

A pine, 30 ins. diam., bears S.43\*E., 65 lks. dist., marked  $\frac{1}{4}$  S 29 B T.

A laurel, 12 ins. diam., bears S.11 $\frac{1}{2}$ \*W., 86 lks. dist., marked  $\frac{1}{4}$  S 30 B T.

Descend SW. slope, 352 ft.

48.75 Draw, course SE.; descend SE. slope.

58.45 Pole fence, bears E. and W.

69.90 Rail fence, bears E. and W.