

## CHAINS

78.15 Old pole fence, bears E. and W.  
 78.38 Intersect the point for cor. of secs. 29, 30, 31, and 32, located by measurement from the original bearing trees. At the exact cor. point.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 29, 30, 31, and 32, with brass cap marked

T29S:R7W  
 S30:S29  
 S31:S32  
 1924

from which ( the original bearing trees)

A black oak, 24 ins. diam., bears S.26\*E., 43 lks. dist. (not S.29\*E.), marks grown over.

A black oak, 36 ins. diam., bears N.4\*W., 48 lks. dist. (not 56 lks. ), marks grown over.

A black oak stump hole, bears N.45\*E., 90 lks. dist.

A pine stump hole, bears S.64\*W., 37 lks. dist.

New bearing trees:

A laurel, 10 ins. diam., bears N.75\*E., 28 lks. dist., marked T. 29 S R 7 W S 29 B T.

A laurel, 12 ins. diam., bears S82\*E., 28 lks. dist., marked T. 29 S R 7 W S 32 B T.

A fir, 6 ins. diam., bears S.19\*W., 7 lks. dist., marked T 29 S R 7 W S 31 B T.

A laurel, 14 ins. diam., bears N.70\*W., 66 lks. dist., marked T 29 S R 7 W S 30 B T.

Land, rolling and mountainous.

Soil, clay loam, 2 nd rate.

Timber, fir, cedar, oak, pine, and laurel.

Undergrowth, hazel, laurel, and fir.

N.88\*52\*W., bet. secs. 30 and 31.

Over rolling land, through heavy timber and dense undergrowth.

Descend SW. slope, 20 ft.

1.30 Road, bears N. and SE.