

125  
X

CHAINS

3.50 Dry draw, course SE.; ascend E. slope, 40 ft.  
 5.40 Top of spur, slopes SE.; descend along S. slope, 30 ft.  
 11.70 Draw, course SE.; ascend E. slope, 252 ft.  
 19.05 Pole fence, bears N. and S.; ascend SE. slope.  
 35.65 Top of ascent; descend SW. slope, 25 ft.  
 39.68 Intersect the point for  $\frac{1}{4}$  sec. cor., located by record bearing and distance from the original SE. bearing tree.

At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   $\frac{S30}{S31}$   
1924

from which ( the original bearing tree)

A black oak, 18 ins. diam., bears S.7\*E., 51 lks. dist., blazes plain, marks grown over and not opened.

New bearing trees:

A laurel 32 ins. diam., bears N.61\*E., 63 lks. dist., marked  $\frac{1}{4}$  S 30 B T.

A black oak, 10 ins. diam., bears S.81\*E., 121 lks. dist., marked  $\frac{1}{4}$  S 31 B T.

Thence from the  $\frac{1}{4}$  sec. cor.

N.69\*57\*W., bet. secs. 30 and 31.

Descend over SW. slope, 132 ft.

12.70 House bears S. 30\*W., 190 lks. dist.

22.19 Proportionate distance, point for W. 1/16 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 4 of Tract No. 55, with brass cap marked

TR 55:  
 $\frac{AP 4:S30}{S31}$  W 1/16  
1924

from which

A fir, 7 ins. diam., bears N.14\*W., 75 lks. dist., marked A P 4 TR 55 B T.

24.70 Head of draw, course NW.; ascend NE. slope, 75 ft.