

Subdivisions, T. 29 S., R. 7 W.

CHAINS

A black oak, 20 ins. diam., bears N.12°E., 90 lks. dist., marked $\frac{1}{4}$ S 29 B T.

A fir, 6 ins. diam., bears S.27°W., 48 lks. dist., marked $\frac{1}{4}$ S 32 B T.

Thence from the $\frac{1}{4}$ sec. cor.

S.88°54'E., bet. secs. 29 and 32.

Descend steep slope SE. 510 ft.

13.00 Road, bears NE. and SW.

13.20 Board fence, bears NE. and SW.

13.30 Enter grain field, bears NE. and SW.

15.20 Pole fence, bears N. and S.; foot of descent; thence over nearly level land.

17.70 Leave grain field, bears NE. and SE.; enter scattering timber and dense undergrowth.

24.10 Olalla Creek, 20 lks. wide, course N.

28.30 Road, bears NE. and SW.; ascend gradually 50 ft.

34.34 Intersect the point for cor. of secs. 28, 29, 32, and 33, located by record bearing and distance from the original SE. bearing tree on which the marks are plain.

At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 28, 29, 32, and 33, with brass cap marked

T29S:R7W
 $\frac{S29:S28}{S32:S33}$
 1924

from which (the original bearing trees)

A black oak, 30 ins. diam., bears S.55°E., 119 lks. dist., marks legible.

Stump holes of NW. and SW bearing trees further evidence the position of the old cor.

New bearing trees:

A white oak, 6 ins. diam., bears N.36 $\frac{1}{2}$ °E., 42 lks. dist., marked T 29 S R 7 W S 28 B T.

A black oak, 10 ins. diam., bears S.51°E., 52 lks. dist., marked T 29 S R 7 W S 33 B T.